Product Information Sheet

trol gear, light-

ing control

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	LLLOAILD KLOOI	-AITON (LO) 2019/2	ots with regard to energ	gy labelling of light
Supplier's name	or trade mark:	Dyberg Larsen		
Supplier's addre	ess: Direktionen,	Fabriksvej 1, 5466	Middelfart Asperup, DK	
Model identifie	r: 1113 - ST2776	В		
Type of light so	urce:			
Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap-type		XTE		
(or other electri	c interface)			
Mains or non-mains:		NMLS	Connected light source (CLS):	No
Colour-tuneable light source:		No	Envelope:	-
High luminance	light source:	No		
Anti-glare shield	d:	No	Dimmable:	No
		Product para	meters	
Parameter		Value	Parameter	Value
		General product p	parameters:	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		2	Energy efficiency class	E
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		275 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power (P _{on}), expressed in W		2,3	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82
Outer dimen-	Height	110	Spectral power dis-	See image
sions without	Width	110	tribution in the	in last page
separate con- trol gear, light-	Depth	110	range 250 nm to 800 nm. at full-load	

nm, at full-load

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,425			
		nates (x and y)	0,398			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	13	Survival factor	1,00			
the lumen maintenance factor	0,98					

(a)'-': not applicable; (b)'-': not applicable;

